

SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

Safety Data Sheets

Identification

Product Name : Latex ink LX101 Black

Order No. : LX101-K-60

Ink Ver.

General Use : Ink for ink jet printer

Product Description : Aqueous ink : 037-W352465 SDS Number

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413 Importer / Distributor Established in Australia

Company Name : MIMAKI SINGAPORE PTE. LTD.

Address : 31 Kaki Bukit Road 3 Singapore 417818 TechLink #02-03

Telephone No. : +65-6508-2789 Emergency Telephone No. : +81-268-64-2281

2. Hazards Identification

[Classification of the substance or mixture]

Physical Hazards

: Not classified Flammable Liquids

Health Hazards

Eye Damage / Irritation : Category 2 Carcinogenicity : Category 2

Specific Target Organ Toxicity : Category 3 (narcotic effects)

(Single Exposure)

Specific Target Organ Toxicity : Category 2

(Repeated Exposure)

The above list does not include category being non-classifiable or not-applicable.

[Label Elements]

Symbol







SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Safety Data Sheets

Signal Word

Warning

Hazard Statements

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs.

Precautionary Statements

[Prevention]

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

[Response]

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/ attention.

P312 Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.

P337+P313 If eye irritation persists: Get medical advice/attention.

[Storage]

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

[Disposal]

P501 Dispose of contents/container in accordance with local regulations.

3. Composition / Information on Ingredients

[Substances]

See section below for composition of Mixtures

Mixtures

No	Chemical Name	Wt%	CAS No.
1	Alcohol solvent series	28-32	Not Available
2	Glycol ether solvents	10-20	Not Available
3	carbon black	1-5	1333-86-4
4	Organic ingredient	1-5	Not Available
5	methyldiethanolamine	0.1-1.5	105-59-9

4. First Aid Measures

[Description of first aid measures]

Eye Contact : If this product comes in contact with the eyes:

Wash out immediately with fresh running water.

Ensure complete irrigation of the eye by keeping eyelids apart and



Product Name: Latex ink LX101 Black

SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

away from eye and moving the eyelids by occasionally lifting the upper and lower lids.

Seek medical attention without delay; if pain persists or recurs seek medical attention.

Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin Contact If skin contact occurs:

Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available).

Seek medical attention in event of irritation.

Inhalation : If fumes or combustion products are inhaled remove from

contaminated area.

Lay patient down. Keep warm and rested.

Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.

Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.

Transport to hospital, or doctor, without delay.

Ingestion : If swallowed do NOT induce vomiting.

If vomiting occurs, lean patient forward or place on left side

(head-down position, if possible) to maintain open airway and prevent

aspiration.

Observe the patient carefully.

Never give liquid to a person showing signs of being sleepy or with

reduced awareness; i.e. becoming unconscious.

Give water to rinse out mouth, then provide liquid slowly and as

much as casualty can comfortably drink.

Seek medical advice.

Indication of Immediate

Medical Attention and

: Treat symptomatically.

Special Treatment

Needed

5. Fire Fighting Measures

[Extinguishing Media]



SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

Safety Data Sheets

Foam, Dry chemical powder, BCF (where regulations permit), Extinguishing Media

Carbon dioxide, Water spray or fog - Large fires only.

[Special hazards arising from the substrate or mixture]

Fire Incompatibility : Avoid contamination with oxidising agents i.e. nitrates, oxidising

acids, chlorine bleaches, pool chlorine etc. as ignition may result

[Advice for firefighters]

Fire Fighting : Alert Fire Brigade and tell them location and nature of hazard.

Wear full body protective clothing with breathing apparatus.

Prevent, by any means available, spillage from entering drains or

water courses.

Use water delivered as a fine spray to control fire and cool adjacent

area.

Avoid spraying water onto liquid pools.

DO NOT approach containers suspected to be hot.

Cool fire exposed containers with water spray from a protected

location.

If safe to do so, remove containers from path of fire.

Equipment should be thoroughly decontaminated after use.

Slight hazard when exposed to heat, flame and oxidisers.

Fire/Explosion Hazard : Combustible.

Will burn if ignited. Combustion products include; carbon monoxide

(CO), carbon dioxide (CO2), other pyrolysis products typical of burning organic material May emit poisonous fumes. May emit

corrosive fumes.

Accidental Release Measures

Personal precautions, : See section 8.

protective equipment and

emergency procedures

Environmental : See section 12.

precautions

[Methods and material for containment and cleaning up]

Minor Spills : Clean up all spills immediately.

Secure load if safe to do so.

Bundle/collect recoverable product.



Product Name: Latex ink LX101 Black

SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

Collect remaining material in containers with covers for disposal.

Major Spills

: Clear area of personnel and move upwind.

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves.

Prevent, by any means available, spillage from entering drains or water course.

Stop leak if safe to do so.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.

Neutralise/decontaminate residue (see Section 13 for specific agent).

Collect solid residues and seal in labelled drums for disposal.

Wash area and prevent runoff into drains.

After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.

If contamination of drains or waterways occurs, advise emergency services.

Minor hazard.

Clear area of personnel.

Alert Fire Brigade and tell them location and nature of hazard.

Control personal contact with the substance, by using protective equipment as required.

Prevent spillage from entering drains or water ways.

Contain spill with sand, earth or vermiculite.

Collect recoverable product into labelled containers for recycling.

Absorb remaining product with sand, earth or vermiculite and place in appropriate containers for disposal.

Wash area and prevent runoff into drains or waterways.

If contamination of drains or waterways occurs, advise emergency services.

Clean up all spills immediately.

Wear protective clothing, safety glasses, dust mask, gloves.

Secure load if safe to do so. Bundle/collect recoverable product.

Use dry clean up procedures and avoid generating dust.

Vacuum up (consider explosion-proof machines designed to be grounded during storage and use).

Water may be used to prevent dusting.

Collect remaining material in containers with covers for disposal.



Product Name: Latex ink LX101 Black

SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

Flush spill area with water.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

7. Handling and Storage

[Precautions for safe handling]

Safe handling : Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Avoid contact with incompatible materials.

When handling, DO NOT eat, drink or smoke.

Keep containers securely sealed when not in use.

Avoid physical damage to containers.

Always wash hands with soap and water after handling.

Work clothes should be laundered separately. Launder contaminated

clothing before re-use.

DO NOT allow clothing wet with material to stay in contact with skin

[Conditions for safe storage, including any incompatibilities]

Storage : Store in original containers.

Keep containers securely sealed.

No smoking, naked lights or ignition sources.

Store locked up.

Store in a well-ventilated place. Keep container tightly closed.

Store away from incompatible materials and foodstuff containers.

Protect containers against physical damage and check regularly for

leaks.

Observe manufacturer's storage and handling recommendations

contained within this SDS.

Incompatibility Strong acids, strong oxidisers, acid anhydrides, oxidising and reducing

agents.

8. Exposure Controls / Personal Protection

[Control parameters]

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source: Singapore Permissible Exposure Limits of Toxic Substances

Ingredient	Material name	TWA	STEL	Peak	Notes
carbon black	Carbon black	3.5 mg/m3	Not	Not	Not



SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

Safety Data Sheets

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
carbon black	Carbon black	9 mg/m3	99 mg/m3	590 mg/m3

Ingredient	Original IDLH	Revised IDLH
Glycol ether solvents	Not Available	Not Available
Alcohol solvent series	Not Available	Not Available
carbon black	N.E. mg/m3 / N.E. ppm	1,750 mg/m3
Organic ingredient	Not Available	Not Available
methyldiethanolamine	Not Available	Not Available

Exposure Controls

Appropriate : Local exhaust ventilation usually required.

Engineering Controls Provide adequate ventilation in warehouse or closed storage area.

Personal protection

Eye and face : Safety glasses with side shields.

protection Chemical goggles.

Contact lenses may pose a special hazard; soft contact lenses may

absorb and concentrate irritants.

Hands/feet protection : Wear chemical protective gloves, e.g. PVC.

Wear safety footwear or safety gumboots, e.g. Rubber

Body protection : P.V.C. apron.

Respiratory Protection : Consult with a health and safety professional for specific respirators

appropriate for your use.

Thermal hazards : Not Available.









9. Physical and Chemical Properties

[Information on basic physical and chemical properties]

- Physical State : liquid Appearance

> : black - Color

Odor : Slight



SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Safety Data Sheets

Odour threshold : Not Available

pH (as supplied) : 9.3-10.3

Melting point / freezing point (°C) : Not Available
Initial boiling point and boiling range : Not Available

(°C)

Flash point (°C) : Not Available Evaporation rate : Not Available : Not Available Flammability Upper Explosive Limit (%) : Not Available Lower Explosive Limit (%) : Not Available : Not Available Vapour pressure (kPa) Solubility in water (g/L) : Not Available Vapour density (Air = 1) : Not Available Relative density (Water = 1) : 1.02-1.04

Partition coefficient n-octanol / water : Not Available Auto-ignition temperature (°C) : Not Available Decomposition temperature : Not Available Viscosity (cSt) : Not Available Molecular weight (g/mol) : Not Available Taste : Not Available : Not Available Explosive properties : Not Available Oxidising properties Surface Tension (dyn/cm or mN/m) : Not Available Volatile Component (%vol) : Not Available : Not Available Gas group : Not Available pH as a solution (1%)

10. Stability and Reactivity

Reactivity : Stable under normal conditions of use.

Chemical Stability : Unstable in the presence of incompatible materials.

Product is considered stable.

: Not Available

Possibility of Hazardous : Hazardous polymerisation will not occur.

Reactions

VOC g/L

Conditions to Avoid : See section 7



Product Name: Latex ink LX101 Black

SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Incompatible Materials : See section 7
Hazardous : See section 5

Decomposition

11. Toxicological Information

Acute Toxicity

	TOXICITY	IRRITATION	
As a product	Not Available	Not Available	
carbon black	Dermal (rabbit) LD50: >3000 mg/kg		
carbon black	Oral (rat) LD50: >8000 mg/kg	Not Available	
	Dermal (rabbit) LD50: >2000 mg/kg	Eye (rabbit) 20 mg open -	
	Dermai (rabbit) LD50: ~2000 mg/kg	irrit.	
methyldiethanolamine	Oral (rat) LD50: 1945 mg/kg	Skin (rabbit) 10 mg/24H	
methylalethanolamine	Orai (rat/ LD50- 1945 mg/kg	open-mild	
		Skin (rabbit) 502 mg open -	
		mild	

[Information on toxicological effects]

Inhaled

: The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.

Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.

Ingestion

: Accidental ingestion of the material may be damaging to the health of the individual.

Skin Contact

: This material can cause inflammation of the skin on contact in some persons.

The material may accentuate any pre-existing dermatitis condition Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.

Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts,



Eye

Chronic

Product Name: Latex ink LX101 Black

SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

: This material can cause eye irritation and damage in some persons.

: There has been concern that this material can cause cancer or mutations, but there is not enough data to make an assessment.

Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.

Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure.

Some glycol esters and their ethers cause wasting of the testicles, reproductive changes, infertility and changes to kidney function. Shorter chain compounds are more dangerous.

Medical Conditions

: CARBON BLACK

Aggravated by Exposure

No significant acute toxicological data identified in literature search.

WARNING: This substance has been classified by the IARC as Group 2B: Possibly Carcinogenic to Humans.

Inhalation (rat) TCLo: 50 mg/m3/6h/90D-I Nil reported

METHYLDIETHANOLAMINE

The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.

PRODUCT & METHYLDIETHANOLAMINE

Asthma-like symptoms may continue for months or even years after exposure to the material ceases.

This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome

(RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria

for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic

individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant.

A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine



SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Safety Data Sheets

challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases. The disorder is characterised by dyspnea, cough and mucus production.

Skin : Data Not Available to make classification

Irritation/Corrosion

Serious Eye : Category 2, as a product

Damage/Irritation

Respiratory or Skin : Data Not Available to make classification

sensitisation

Mutagenicity : Data Not Available to make classification

Carcinogenicity : Category 2, as a product

Reproductivity : Data Not Available to make classification

STOT – Single : Category 3, as a product

Exposure

STOT – Repeated : Category 2, as a product

Exposure

Aspiration Hazard : Data Not Available to make classification

12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch. Toxicity

Ingredient	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50	96	Fish	>100mg/L	2
	NOEC	720	Fish	17mg/L	2
carbon black	EC50	48	Crustacea	>100mg/L	2
	EC50	384	Crustacea	$4.9 \mathrm{mg/L}$	2
	EC50	96	Algae or other aquatic	95mg/L	2



SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Safety Data Sheets

			plants		
	LC50	96	Fish	$320 \mathrm{mg/L}$	1
	EC50	48	Crustacea	=230mg/L	1
methyldietha	EC50	96	Algae or other aquatic plants	=20mg/L	1
nolamine	EC20	96	Algae or other aquatic plants	=7.4mg/L	1
	NOEC	72	Algae or other aquatic plants	6.25mg/L	2

Legend: Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity

Mobility : No information available for the product.

Persistence and : No information available for the product.

Degradability

Bioaccumulative : No information available for the product.

Potential

Other Adverse Effects : No information available for the product.

13. Disposal Considerations

Disposal Methods : Dispose in accordance with all applicable regulations. Empty

containers may contain product residue.

Do not dump this product into sewers, on the ground or into any body

of water.

14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Land transport (UN) : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

(ICAO-IATA / DGR)

Sea transport : NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

(IMDG-Code / GGVSee)

Transport in bulk : Not Applicable



Product Name: Latex ink LX101 Black SDS No. 037-W352465 First issue: 2017/05/31

Revised: 2017/07/26

according to Annex II of MARPOL and the IBC code

Marine Pollutant : No

15. Regulatory Information

[Safety, health and environmental regulations / legislation specific for the substance or mixture]

Chemical Name	Regulatory	
	International Agency for Research on Cancer (IARC) - Agents	
CARBON BLACK(1333-86-4)	Classified by the IARC Monographs	
	Singapore Permissible Exposure Limits of Toxic Substances	
METHYLDIETHANOLAMINE	NT 4 A 1' 11	
(105-59-9)	Not Applicable	

[National Inventory]

Australia - AICS	: Y
Canada - DSL	: N
Canada - NDSL	: Y
China - IECSC	: N
Europe - EINEC / ELINCS / NLP	: Y
Japan - ENCS	: Y
Korea - KECI	: Y
New Zealand - NZIoC	: N
Philippines - PICCS	: N
USA - TSCA	: Y

Y = All ingredients are on the inventory

N = Not determined or one or more ingredients are not

on the inventory and are not exempt from listing(seespecific ingredients in brackets)

16. Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.



SDS No. 037-W352465 First issue: 2017/05/31 Revised: 2017/07/26

Safety Data Sheets

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.