

Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23 Revised: 2024/01/30 Safety Data Sheets

### Identification

**Product Name** : BS4 ink Black

Order No. : BS4-K-60 / BS4-K-2L

Ink Ver. :2

General Use : Ink for ink jet printer **Product Description** : Solvent pigment ink

SDS Number : 037-S181266

Manufacture

Company Name : Mimaki Engineering Co., Ltd.

Address : 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 JAPAN

Telephone No. : +81-268-64-2413

Importer / Distributor Established in USA

Company Name : MIMAKI USA, INC.

Address : 150 Satellite Boulevard NE, suite A, Suwanee, Georgia 30024,

U.S.A.

Telephone No. : +1-678-730-0170

Emergency Telephone No. : +1 866 928 0789 (within United States only, Toll free)

+1 215 207 0061

#### 2. Hazards Identification

[HCS Classification]

Physical Hazards

Flammable Liquids : Category 4

**Health Hazards** 

Serious Eye Damage / Irritation : Category 2A : Category 2 Carcinogenicity Sensitization - Skin : Category 1

Specific Target Organ Toxicity : Category 2(central nervous system)

(Single Exposure)

Specific Target Organ Toxicity : Category 1 (lungs)

- Repeated Exposure

Hazardous to the aquatic environment : Category 3

- acute hazard



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

# Safety Data Sheets

Hazardous to the Aquatic

: Category 2

Environment - Long Term Hazard

The above list does not include category being non-classifiable or not-applicable.

#### [HCS Label Elements]

Symbol







#### Signal Word DANGER

#### **Hazard Statements**

H227 Combustible liquid.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H351 Suspected of causing cancer.

H371 May cause damage to organs (central nervous system)

H372 Causes damage to organs through prolonged or repeated exposure (lungs).

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

#### **Precautionary Statements**

[Prevention]

P201 Obtain SDS (Safety Data Sheet) and printer's operation manual before use.

P202 Do not handle until all safety precautions have been read and understood.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P260 Do not breathe gas/mist.

P264 Wash hands and eyes thoroughly after handling.

P270 Do not eat, drink, or smoke when using this product.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

 $P280 \ Wear \ protective \ gloves/protective \ clothing/eye \ protection/face \ protection.$ 

Response

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P314 Get medical advice/attention if you feel unwell.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P370+P378 In case of fire: Use appropriate media for extinction.

P391 Collect spillage.

[Storage]

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

[Disposal]



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23 Revised: 2024/01/30

# Safety Data Sheets

P501 Dispose of contents/container in accordance with local/regional/national/international regulation (to be specified).

NFPA Rating (scale 0-4)

Health = 2

Flammability = 2

Instability = 0

Special =



CANADIAN WHMIS SYMBOLS: B3, D2A, D2B



#### 3. Composition / Information on Ingredients

No	Chemical Name	Wt%	CAS No.
1	Glycol ether solvents	70-80	Trade Secret
2	$\gamma$ -Butyrolactone	10-20	96-48-0
3	Carbon black	1-10	Trade Secret
4	Chlorinated Ethylene-Vinyl Acetate Copolymer (CEVA)	1-10	Trade Secret
5	Acrylic type resine	1-10	Trade Secret
6	Additive 1	0.1-5	Trade Secret
7	Additive 2	0.1-5	Trade Secret
8	Additive 3	0.1-5	Trade Secret

The chemical identity and/or percentage of composition is being withheld as a trade secret.

#### 4. First Aid Measures

Description of Necessary Measures

Inhalation : Remove person to fresh air and keep comfortable for breathing. Give

artificial respiration if not breathing. Call a POISON CENTER or

doctor/physician.

Eye Contact : Flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If

irritation or pain persists after fifteen minutes of eye irrigation, seek



Product Name: BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

medical attention.

Skin Contact : Wash with plenty of soap and water. If skin irritation or rash occurs:

Get medical advice/attention. Take off contaminated clothing and

wash before re-use.

Ingestion : If swallowed, get medical attention.

Most Important Symptoms/Effects

Acute eye irritation, central nervous system damage, allergic skin reaction

Delayed : cancer, lung damage, allergic skin reaction

Indication of Immediate

: Treat symptomatically and supportively.

Medical Attention and Special Treatment Needed, If Needed

#### Fire Fighting Measures

Flammable Properties : Flash Point: 70 °C

> Auto Ignition Temperature: 169 °C (Glycol ether type solvent) Flammable Point:2.5vol%-33.0Vol% (Glycol ether type solvent)

Extinguishing Media : carbon dioxide, regular dry powder, regular dry chemical, water

spray, alcohol resistant foam.

Unsuitable Extinguishing

: Do not scatter spilled material with high-pressure water streams.

Media

Special Hazards Arising

from the Chemical

**Hazardous Combustion** 

**Products** 

: Combustible liquid and vapor. Irritating fumes and gases may be

released upon thermal processing or during combustion.

: Combustion: oxides of carbon, oxides of nitrogen

Fire Fighting Measures

: Move container from fire area if it can be done without risk. Do not

scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away

from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after

fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry.

Let the fire burn. Withdraw immediately in case of rising sound from

venting safety device or any discoloration of tanks due to fire.



Product Name: BS4 ink Black

SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

# Safety Data Sheets

Special Protective

Equipment and

Precautions for **Firefighters** 

: Wear full protective fire fighting gear including self contained

breathing apparatus (SCBA) for protection against possible exposure.

#### Accidental Release Measures

Personal Precautions,

Protective Equipment

and Emergency

Procedures

Methods and Materials

for Containment and

Cleaning Up

: Wear personal protective clothing and equipment, see Section 8.

Eliminate all ignition sources if safe to do so. Stop leak if possible

without personal risk. Reduce vapors with water spray.

Small spills: Absorb with sand or other non-combustible material.

Collect spilled material in appropriate container for disposal.

Large spills: Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low

### Handling and Storage

Precautions for Safe

Handling

: Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Obtain special instructions before use. Do not handle until

all safety precautions have been read and understood. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat,

drink, or smoke when using this product. Wear protective

gloves/clothing and eye/face protection. Wash thoroughly after

handling.

areas.

Conditions for Safe Storage, including any Incompatibilities

: Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Grounding and bonding required. Store locked up.

Keep separated from incompatible substances.

Incompatible materials include acids, bases, oxidizing materials, and

halogens.

#### Exposure Controls / Personal Protection



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

#### **Exposure Limit Values**

#### Carbon black (1333-86-4)

ACGIH: 3 mg/m3 TWA (inhalable fraction)

OSHA: 3.5 mg/m3 TWA

NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA

(Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

Mexico: 3.5 mg/m3 TWA LMPE-PPT

7 mg/m3 STEL [LMPE-CT]

Component Biological : There are no biological limit values for the component(s) of this

Limit Values product.

#### **Exposure Controls**

Occupational Exposure Controls

Appropriate : Provide local exhaust or process enclosure ventilation system.

Engineering Controls Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Respiratory Protection : Consult with a health and safety professional for specific respirators

appropriate for your use.

Vapor Respirator

Glove : Wear appropriate chemical resistant gloves.

Recommendations



Eye /Face : Wear splash resistant safety goggles with a faceshield. Provide an

Protection emergency eye wash fountain and quick drench shower in the

immediate work area.

Safety Glasses

Skin Protection : Wear appropriate chemical resistant clothing.



**Environmental Exposure Controls** 



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

Physical and Chemical Properties

Appearance - Physical State : liquid

- Color : black

Odor : solvent odor
pH : Not Applicable
Boiling Point / Boiling Range : Not available
Melting Point / Melting Range : Not available

Flash Point :  $70^{\circ}$ C

Auto ignition temperature : 169 °C (Glycol ether type solvent)

Flammability (Solid, Gas) : Not available

Upper / Lower Flammability or : 2.5 vol %-33.0 vol % (Glycol ether type solvent)

**Explosive Limits** 

Vapor Pressure : <=0.1 kPa (20°C) (Glycol ether type solvent)

Density : 0.977 g/cm3
Water Solubility : Not available

Viscosity : 4.0-4.5 mPa/s @25 °C

Vapor Density : Not available Evaporation Rate : Not available

#### 10. Stability and Reactivity

Reactivity : No reactivity hazard is expected.

Conditions to Avoid : Avoid flames, sparks, and other sources of ignition. Avoid contact

with incompatible materials.

Stability : Stable under normal conditions of use.

Materials to Avoid : acids, bases, oxidizing materials, halogens

Hazardous Reactions / : Combustion: oxides of carbon, oxides of nitrogen

**Decomposition Products** 

#### 11. Toxicological Information

**Acute Toxicity** 

Component Analysis - LD50/LC50



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

## Safety Data Sheets

The component(s) of this material have been reviewed in various sources and the following selected endpoints are published:

Glycol ether solvents (Trade Secret)

Oral LD50 Rat 6500 µL/kg

 $\gamma$  -Butyrolactone (96-48-0)

Oral LD50 Rat 1540 mg/kg Inhalation LC50 Rat >5100 mg/m3 4 h

Additive 2 (Trade Secret)

Oral LD50 Rat 40 g/kg Dermal LD50 Rabbit >20 mL/kg

Carbon black (1333-86-4)

Oral LD50 Rat >15400 mg/kg

Information on Likely Routes of Exposure

Inhalation : irritation, headache, cancer, dizziness, drowsiness, lung

damage.

Ingestion : vomiting, nausea.

Skin Contact : irritation, skin disorders, allergic reactions.

Eye Contact : irritation

Immediate Effects : eye irritation, central nervous system damage, allergic

: No information available for the product.

skin reaction.

 $\label{eq:cancer} \mbox{Delayed Effects} \qquad \qquad \mbox{: lung damage, cancer, allergic skin reaction.}$ 

Medical Conditions Aggravated

by Exposure

Irritation/Corrosivity Data : eye irritation.

Respiratory Sensitization : No information available for the product.

Dermal Sensitization : May cause an allergic skin reaction.

Germ Cell Mutagenicity : No information available for the product.

Carcinogenicity

Component Carcinogenicity

#### $\gamma$ -Butyrolactone (96-48-0)

IARC: Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 3 (not classifiable))

#### Chlorinated Ethylene-Vinyl Acetate Copolymer (CEVA) (Trade Secret)

IARC: Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

#### Carbon black (1333-86-4)

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

IARC: Monograph 93 [2010]; Monograph 65 [1996]

(Group 2B (possibly carcinogenic to humans))

DFG: Category 3B (could be carcinogenic for man, inhalable fraction)



SDS No. 037-S181266 First issue: 2016/03/23 Revised: 2024/01/30

Product Name: BS4 ink Black

**OSHA:** Present

Reproductive Toxicity

No information available for the product.

Specific Target Organ Toxicity - Single Exposure

central nervous system.

Specific Target Organ Toxicity - Repeated Exposure

Lungs.

**Aspiration Hazard** 

No information available for the product.

### 12. Ecological Information

Handling is noted because it might influence the environment when leaking and abandoning it. Especially, note that the product doesn't flow directly to ground, the river, and the drain ditch.

**Ecotoxicity** : Harmful to aquatic life.

Toxic to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

#### $\gamma$ -Butyrolactone (96-48-0)

Algae: 72 Hr EC50 Desmodesmus subspicatus: 360 mg/L;

96 Hr EC50 Desmodesmus subspicatus: 79 mg/L

Invertebrate: 48 Hr EC50 Daphnia magna Straus: >500 mg/L

#### Additive 2 (Trade Secret)

Algae: 72 Hr EC50 Desmodesmus subspicatus: 8 mg/L

Mobility : No information available for the product. Persistence and : No information available for the product.

Degradability

Bioaccumulative : No information available for the product.

Potential

Other Adverse Effects : No additional information is available.

#### 13. Disposal Considerations

Disposal Methods : Dispose in accordance with all applicable regulations.

Component Waste : The U.S. EPA has not published waste numbers for this product's

Numbers components.

Disposal of : Empty containers may contain product residue. Dispose in



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

# Safety Data Sheets

Contaminated accordance with all applicable regulations.

Packaging

Comply with all USA, national and local regulations.

Do not dump this product into sewers, on the ground or into any body of water.

#### 14. Transport Information

Check a thing without a leak in a container.

Perform prevention of collapse of cargo surely.

Us Department of Transportation (DOT)

Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

UN/NA Number : UN3082 / NA1993 \*1

Hazardous Class : 9
Packing Group (PG) : III
Label(s) Required : 9

\*1 Class combustible liquid (NA1993), Packing group III for quantities of 450 liters (119 gallons) or more; not regulated for smaller quantities.

TDG Information

Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

UN Number : UN3082

Hazardous Class : 9
Packing Group (PG) : III
Label(s) Required : 9

**IATA Information** 

Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

UN Number : UN3082

Hazardous Class : 9
Packing Group (PG) : III
Label(s) Required : 9

**ICAO** Information

Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

UN Number : UN3082

Hazardous Class : 9
Packing Group (PG) : III
Label(s) Required : 9



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23 Revised: 2024/01/30

## Safety Data Sheets

**IMDG** Information

Shipping Name : Environmentally hazardous substance, liquid, n.o.s.

UN Number : UN3082

Hazardous Class : 9
Packing Group (PG) : III
Label(s) Required : 9

Marine Pollutant : γ - Butyrolactone (96-48-0)

IBC Code: Category Y

Remarks : Single or inner packaging less than 5 L (liquid) or 5 kg net (solids) is

excepted from Dangerous Goods regulations.

Refer to ICAO/IATA A197, IMDG 2.10.2.7, ADR SP 375.

#### 15. Regulatory Information

U.S. Federal : None of this products components are listed under SARA Sections

Regulations 302/304 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR

370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4),

TSCA 12(b), or require an OSHA process safety plan.

SARA 311/312 : Acute Health: Yes Chronic Health: No Fire: Yes Pressure: No

Reactive: No

U.S. State Regulations : The following components appear on one or more of the following

state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Carbon black	1333-86-4	Yes	Yes	Yes	Yes	Yes

California Proposition

WARNING:

65



This product can expose you to chemicals including Carbon black, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

Canada : WHMIS CLASSIFICATION: B3, D2A, D2B.

Canadian WHMIS Ingredient Disclosure List (IDL)

: Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which fall under WHMIS criteria specified in the Controlled Products Regulations and present above the threshold limits listed on the IDL.



Product Name:BS4 ink Black SDS No. 037-S181266 First issue: 2016/03/23

Revised: 2024/01/30

#### Carbon black (1333-86-4)

1 %

**Chemical Inventory Listings** 

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PHIL	JP	KR	CN	NZ
*	Trade Secret	Yes	NSL	EIN	No		Yes	No	Yes	Yes
Glycol ether solvents	Trade Secret	res	Nor	EIN	100	No	res	100	res	res
γ -Butyrolactone	96-48-0	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Additive 2	Trade Secret	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Additive 3	Trade Secret	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Carbon black	1333-86-4	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Chlorinated Ethylene-Vinyl	Trade Secret	Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	Yes
Acetate Copolymer (CEVA)										

#### 16. Other Information

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS - Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) - European List of Notified Chemical Substances; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LC50 - Lethal Concentration, 50%; LD50 - Lethal Dose, 50%; LEL - Lower Explosive Limit; LOLI - List Of LIsts<sup>TM</sup> - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit

#### Other Information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of Mimaki Engineering Corporation.

It relates only to the specific material designated herein, and does not relate to use in combination with any other material or process.

Mimaki Engineering Corporation assumes no legal responsibility for use or reliance upon this information.