

Safety Data Sheets

* * *Section 1 - IDENTIFICATION* * *

Product Identifier: BS3 ink Black

Product Description

SPC-0667K / SPC-0693K

Product Use

Pigment ink for ink jet printer **Restrictions on Use**

None known.

Manufacturer Information

Mimaki Engineering Co., Ltd 2182-3 Shigeno-otsu, Tomi-shi, Nagano 389-0512 Japan Telephone number: +81-268-64-2413

Telephone number: +65-6508-2789

Importer / Distributor Information

MIMAKI SINGAPORE PTE. LTD. 31 Kaki Bukit Road 3 Singapore 417818 TechLink #02-03

Emergency telephone number

+65 3165 2217 (within Singapore only) +65 3158 1074

* * *Section 2 - HAZARDS IDENTIFICATION* * *

SPRING/SS 586-2:2014

Serious Eye Damage/Eye Irritation, Category 1 Carcinogenicity, Category 2 Toxic to reproduction, Category 1B Specific Target Organ Toxicity - Single Exposure, Category 1 (blood, central nervous system, systemic toxicity) Specific Target Organ Toxicity - Single Exposure, Category 2 (kidneys and hematopoietic system) Specific Target Organ Toxicity - Single Exposure, Category 3 (respiratory tract) Specific Target Organ Toxicity - Repeated Exposure, Category 1 (lungs) Specific Target Organ Toxicity - Repeated Exposure, Category 2 (blood and kidneys)

LABEL ELEMENTS





Signal Word DANGER Hazard Statement(s) H318 Causes serious eye damage. H351 Suspected of causing cancer.



Product Name: BS3 ink Black SDS No. 037-S131168 First issue: 2016/02/12 Revised: 2023/01/10

H360 May damage fertility or the unborn child.

H370 Causes damage to blood, central nervous system, and body

H371 May cause damage to kidneys and hematopoietic system.

H335 May cause respiratory irritation.

H372 Causes damage to lungs through prolonged or repeated exposure.

H373 May cause damage to blood and kidneys through prolonged or repeated exposure.

Precautionary Statement(s)

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P271 Use only outdoors or in a well-ventilated area.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P264 Wash thoroughly after handling.

Response

P308+P313 IF exposed or concerned: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/physician.

Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations. **Other Hazards Which Do Not Result in Classification**

None known.

* * *Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS* * *

CAS	Component	Percent			
112-07-2	Ethylene glycol monobutyl ether acetate	50-60			
96-48-0	γ-Butyrolactone	15-25			
108-65-6	Propylene glycol monomethyl ether acetate	15-25			
1333-86-4	Carbon black	1-10			
Trade Secret	Additives	0.1-5			
Trade Secret	Vinyl chloride-Vinyl acetate copolymer	1-10			

* * *Section 4 - FIRST AID MEASURES* * *

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin



Product Name: BS3 ink Black SDS No. 037-S131168 First issue: 2016/02/12 Revised: 2023/01/10

Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Note to Physicians

Treat symptomatically and supportively.

Symptoms: Immediate

eye damage, respiratory tract irritation, blood damage, central nervous system damage, systemic toxicity damage, kidney damage, hematopoietic effects

Symptoms: Delayed

cancer, reproductive effects, lung damage, blood damage, kidney damage

* * *Section 5 - FIRE FIGHTING MEASURES* * *

Flammable Properties

Combustible liquid and vapor.

Extinguishing Media

carbon dioxide, regular dry chemical, water spray, alcohol resistant foam

Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

Hazardous Combustion Products

Combustion: oxides of carbon

* * *Section 6 - ACCIDENTAL RELEASE MEASURES* * *

Personal Precautions

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Methods for Containment

Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray.

Cleanup Methods

Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. **Large spills:** Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.



Safety Data Sheets

* * *Section 7 - HANDLING AND STORAGE* * *

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not breathe vapor or mist. Use only outdoors or in a well-ventilated area. Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke when using this product. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Avoid release to the environment.

Conditions for Safe Storage

Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Grounding and bonding required. Store locked up. Keep separated from incompatible substances.

Incompatibilities: acids, bases, oxidizing materials, halogens, amines

* * *Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION* * *

Component Exposure Limits

Ethylene glycol monobutyl ether acetate (112-07-2)

ACGIH: 20 ppm TWA

Carbon black (1333-86-4)

Singapore: 3.5 mg/m3 PEL

ACGIH: 3 mg/m3 TWA (inhalable fraction)

Biological exposure limits

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

Wear appropriate chemical resistant clothing.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Respiratory Protection

Consult with a health and safety professional for specific respirators appropriate for your use.

* * *Section 9 - PHYSICAL AND CHEMICAL PROPERTIES* * *

Physical State:	Liquid	: black liquid			
Color:	black	Physical Form:	liquid		
Odor:	solvent odor	Odor Threshold:	Not available		
pH:	Not available	Melting Point:	<-30°C		
Boiling Point:	145~209 ℃	Flash Point:	65±1 °C		



Decomposition	Not available	Evaporation Rate:	Not available		
Temperature:					
LEL:	Not available	UEL:	Not available		
Vapor Pressure:	0.493kPa (20 °C)	Vapor Density (air = 1):	Not available		
Density:	Not available	Specific Gravity (water =	0.995±0.01 (25 ℃)		
		1):			
Water Solubility:	Water Solubility: Not available		Not available		
Coeff. Water/Oil Dist:	Not available	Auto Ignition	Not available		
		Temperature:			
Viscosity:	4.0±0.3 mPa∙s (25 °C)	Volatility:	Not available		
Oxidizing Properties:	Not available	Explosive Properties:	Not available		
Flammability (solid, gas):	Not applicable				

Other Property Information

No additional information is available.

* * *Section 10 - STABILITY AND REACTIVITY* * *

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks, and other sources of ignition. Containers may rupture or explode if exposed to heat. Avoid contact with incompatible materials.

Materials to Avoid (Incompatibilities)

acids, bases, oxidizing materials, halogens, amines

Hazardous Decomposition:

Combustion: oxides of carbon

* * *Section 11 - TOXICOLOGICAL INFORMATION* * *

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The component(s) of this material have been reviewed in various sources and the following selected endpoints are published:

Ethylene glycol monobutyl ether acetate (112-07-2)

Oral LD50 Rat 2400 mg/kg; Dermal LD50 Rabbit 1480 mg/kg

Propylene glycol monomethyl ether acetate (108-65-6)

Dermal LD50 Rabbit >5 g/kg; Oral LD50 Rat 8532 mg/kg

γ-Butyrolactone (96-48-0)

Oral LD50 Rat 1540 mg/kg; Inhalation LC50 Rat >5100 mg/m3 4 h (no deaths occurred)

Carbon black (1333-86-4)

Oral LD50 Rat >15400 mg/kg

Immediate Effects

eye damage, respiratory tract irritation, blood damage, central nervous system damage, systemic toxicity damage,



kidney damage, hematopoietic effects

Delayed Effects

cancer, reproductive effects, lung damage, blood damage, kidney damage

Irritation/Corrosivity Data

eye damage, respiratory tract irritation

Respiratory Sensitizer

No information available for the product.

Dermal Sensitizer

No information available for the product.

Carcinogenicity

Component Carcinogenicity

Ethylene glycol monobutyl ether acetate (112-07-2)

- ACGIH: A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans
 - DFG: Category 4 (no significant contribution to human cancer)

γ-Butyrolactone (96-48-0)

IARC: Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 3 (not classifiable))

Carbon black (1333-86-4)

- ACGIH: A3 Confirmed Animal Carcinogen with Unknown Relevance to Humans
 - IARC: Monograph 93 [2010]; Monograph 65 [1996] (Group 2B (possibly carcinogenic to humans))
 - DFG: Category 3B (could be carcinogenic for man, inhalable fraction)
- **OSHA:** Present

Vinyl chloride-Vinyl acetate copolymer (Trade Secret)

IARC: Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

Mutagenic Data

No information available for the product.

Reproductive Effects Data

Available data characterizes components of this product as reproductive hazards.

Specific Target Organ Toxicity - Single Exposure

blood, central nervous system, systemic toxicity, kidneys, hematopoietic system, respiratory tract

Specific Target Organ Toxicity - Repeated Exposure

lungs, blood, kidneys

Aspiration Hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

respiratory disorders

* * *Section 12 - ECOLOGICAL INFORMATION* * *

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Ethylene glycol monobutyl ether acetate (112-07-2)

Algae: 72 Hr EC50 Desmodesmus subspicatus: >500 mg/L

Invertebrate: 48 Hr EC50 Daphnia magna: 37 mg/L

Propylene glycol monomethyl ether acetate (108-65-6)

Fish: 96 Hr LC50 Pimephales promelas: 161 mg/L [static]



Invertebrate: 48 Hr EC50 Daphnia magna: >500 mg/L

γ-Butyrolactone (96-48-0)

Algae: 72 Hr EC50 Desmodesmus subspicatus: 360 mg/L; 96 Hr EC50 Desmodesmus subspicatus: 79 mg/L

Invertebrate: 48 Hr EC50 Daphnia magna Straus: >500 mg/L

Bioaccumulation

No information available for the product.

Bioconcentration

No information available for the product.

Biodegradation

No information available for the product.

Persistence

No information available for the product.

Mobility

No information available for the product.

Other Information

No additional information is available.

* * *Section 13 - DISPOSAL CONSIDERATIONS* * *

Disposal Methods

Dispose in accordance with all applicable regulations.

Component Waste Information

There is no applicable waste information for this product's components.

* * *Section 14 - TRANSPORT INFORMATION* * *

IATA Information

Not regulated as dangerous goods for transport.

ICAO Information

Not regulated as dangerous goods for transport.

IMDG Information

Not regulated as dangerous goods for transport.

Marine Pollutant

Ethylene glycol monobutyl ether acetate (112-07-2)

IBC Code: Category Y

Propylene glycol monomethyl ether acetate (108-65-6)

IBC Code: Category Z

γ-Butyrolactone (96-48-0)

IBC Code: Category Y

* * *Section 15 - REGULATORY INFORMATION* * *

Singapore Regulations

Component Analysis

Propylene glycol monomethyl ether acetate (108-65-6)

Petroleum and Flammable	3 (regulated under Propylene glycol monomethyl ether acetate); 3
Materials - Hazard Classes:	
Petroleum and Flammable	SCDPEA3272L1 (regulated under Propylene glycol monomethyl ether
Materials - Regulated	acetate); SCDMPA1993L2



Products:

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PHIL	JP	KR	CN	NZ
Ethylene glycol	112-07-2	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
monobutyl ether acetate										
Propylene glycol	108-65-6	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
monomethyl ether										
acetate										
γ-Butyrolactone	96-48-0	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Carbon black	1333-86-4	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Vinyl chloride-Vinyl	Trade Secret	Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	Yes
acetate copolymer										

* * *Section 16 - OTHER INFORMATION* * *

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS -Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) -European List of Notified Chemical Substances; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LC50 - Lethal Concentration, 50%; LD50 - Lethal Dose, 50%; LEL - Lower Explosive Limit; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK -Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit

Disclaimer

The information set forth in this Safety Data Sheet does not purport to be all-inclusive and should be used only as a guide. While the information and recommendations set forth herein are believed to be accurate, the company makes no warranty regarding such information and recommendations and disclaims all liability from reliance thereon.

End of Sheet 037-S131168