

Safety Data Sheets

Section 1 - IDENTIFICATION

Product Identifier: CS100 ink Yellow

Product Description

CS100-Y-BB

Product Use

Pigment ink for ink jet printer

Restrictions on Use

None known.

Manufacturer Information

Mimaki Engineering Co., Ltd
2182-3 Shigeno-otsu, Tomi-shi, Nagano
389-0512 Japan

Telephone number: +81-268-64-2413

Importer / Distributor Information

MIMAKI SINGAPORE PTE. LTD.
31 Kaki Bukit Road 3 Singapore 417818 TechLink #02-03

Telephone number: +65-6508-2789

Emergency telephone number

+65 3165 2217 (within Singapore only)
+65 3158 1074

Section 2 - HAZARDS IDENTIFICATION

SPRING/SS 586-2:2014

Serious Eye Damage/Eye Irritation, Category 1

Toxic to reproduction, Category 1B

Specific Target Organ Toxicity - Single Exposure, Category 1 (blood, central nervous system, systemic toxicity)

Specific Target Organ Toxicity - Single Exposure, Category 2 (kidneys and hematopoietic system)

Specific Target Organ Toxicity - Repeated Exposure, Category 2 (blood and kidneys)

LABEL ELEMENTS

Symbol(s)



Signal Word

DANGER

Hazard Statement(s)

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H370 Causes damage to blood, central nervous system, and body

H371 May cause damage to kidneys and hematopoietic system.

H373 May cause damage to blood and kidneys through prolonged or repeated exposure.

Safety Data Sheets

Precautionary Statement(s)

Prevention

- P201** Obtain special instructions before use.
- P202** Do not handle until all safety precautions have been read and understood.
- P260** Do not breathe dust/fume/gas/mist/vapours/spray.
- P270** Do not eat, drink or smoke when using this product.
- P280** Wear protective gloves/protective clothing/eye protection/face protection.
- P264** Wash thoroughly after handling.

Response

- P308+P313** IF exposed or concerned: Get medical advice/attention.
- P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310** Immediately call a POISON CENTER or doctor/physician.

Storage

- P405** Store locked up.

Disposal

- P501** Dispose of contents/container in accordance with local/regional/national/international regulations.

Other Hazards Which Do Not Result in Classification

None known.

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component	Percent
112-07-2	Ethylene glycol monobutyl ether acetate	50-60
108-65-6	Propylene glycol monomethyl ether acetate	15-25
96-48-0	γ -Butyrolactone	15-25
Trade Secret	Additives	0.1-5
Trade Secret	Azo-Nickel complex pigment	1-10
Trade Secret	Vinyl chloride-Vinyl acetate copolymer	1-10

Section 4 - FIRST AID MEASURES

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician.

Skin

Wash with plenty of soap and water. Take off contaminated clothing and wash before re-use. Get medical attention if irritation develops.

Eyes

Flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

Ingestion

If swallowed, get medical attention.

Note to Physicians

Treat symptomatically and supportively.

Symptoms: Immediate

eye damage, blood damage, central nervous system damage, systemic toxicity damage, kidney damage, hematopoietic effects

Safety Data Sheets

Symptoms: Delayed

reproductive effects, blood damage, kidney damage

Section 5 - FIRE FIGHTING MEASURES

Flammable Properties

Combustible liquid and vapor.

Extinguishing Media

carbon dioxide, regular dry chemical, water spray, alcohol resistant foam

Unsuitable Extinguishing Media

Do not scatter spilled material with high-pressure water streams.

Protective Equipment and Precautions for Firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk. Do not scatter spilled material with high-pressure water streams. Cool containers with water spray until well after the fire is out. Stay away from the ends of tanks. Avoid inhalation of material or combustion by-products. For fires in cargo or storage area: Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. If this is impossible then take the following precautions: Keep unnecessary people away, isolate hazard area and deny entry. Let the fire burn. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire.

Hazardous Combustion Products

Combustion: oxides of carbon

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions

Wear personal protective clothing and equipment, see Section 8.

Environmental Precautions

Avoid release to the environment.

Methods for Containment

Eliminate all ignition sources if safe to do so. Stop leak if possible without personal risk. Reduce vapors with water spray.

Cleanup Methods

Small spills: Absorb with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. **Large spills:** Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Do not breathe vapor or mist. Avoid contact with eyes, skin and clothing. Do not eat, drink, or smoke when using this product. Wear protective gloves and eye/face protection. Wash thoroughly after handling. Avoid release to the environment.

Conditions for Safe Storage

Store and handle in accordance with all current regulations and standards. Store in a well-ventilated place. Keep container tightly closed. Keep cool. Grounding and bonding required. Store locked up. Keep separated from incompatible substances.

Incompatibilities: acids, bases, oxidizing materials, amines

Safety Data Sheets

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Ethylene glycol monobutyl ether acetate (112-07-2)

ACGIH: 20 ppm TWA

Biological exposure limits

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face

Wear splash resistant safety goggles with a faceshield. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Protective Clothing

Wear appropriate chemical resistant clothing.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Respiratory Protection

Consult with a health and safety professional for specific respirators appropriate for your use.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid	Appearance:	yellow liquid
Color:	yellow	Physical Form:	liquid
Odor:	solvent odor	Odor Threshold:	Not available
pH:	Not available	Melting Point:	<-30°C
Boiling Point:	145~209 °C	Flash Point:	67±1 °C
Decomposition Temperature:	Not available	Evaporation Rate:	Not available
LEL:	Not available	UEL:	Not available
Vapor Pressure:	0.493kPa (20 °C)	Vapor Density (air = 1):	Not available
Density:	Not available	Specific Gravity (water = 1):	0.995±0.01 (25 °C)
Water Solubility:	Not available	Log KOW:	Not available
Coeff. Water/Oil Dist:	Not available	Auto Ignition Temperature:	Not available
Viscosity:	4.0±0.3 mPa·s (25 °C)	Volatility:	Not available
Oxidizing Properties:	Not available	Explosive Properties:	Not available
Flammability (solid, gas):	Not applicable		

Other Property Information

No additional information is available.

Section 10 - STABILITY AND REACTIVITY

Reactivity

No reactivity hazard is expected.

Safety Data Sheets

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Avoid flames, sparks, and other sources of ignition. Containers may rupture or explode if exposed to heat. Avoid contact with incompatible materials.

Materials to Avoid (Incompatibilities)

acids, bases, oxidizing materials, amines

Hazardous Decomposition:

Combustion: oxides of carbon

* * *Section 11 - TOXICOLOGICAL INFORMATION* * *

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The component(s) of this material have been reviewed in various sources and the following selected endpoints are published:

Ethylene glycol monobutyl ether acetate (112-07-2)

Oral LD50 Rat 2400 mg/kg; Dermal LD50 Rabbit 1480 mg/kg

Propylene glycol monomethyl ether acetate (108-65-6)

Dermal LD50 Rabbit >5 g/kg; Oral LD50 Rat 8532 mg/kg

γ -Butyrolactone (96-48-0)

Oral LD50 Rat 1540 mg/kg; Inhalation LC50 Rat >5100 mg/m³ 4 h (no deaths occurred)

Immediate Effects

eye damage, blood damage, central nervous system damage, systemic toxicity damage, kidney damage, hematopoietic effects

Delayed Effects

reproductive effects, blood damage, kidney damage

Irritation/Corrosivity Data

eye damage

Respiratory Sensitizer

No information available for the product.

Dermal Sensitizer

No information available for the product.

Carcinogenicity

Component Carcinogenicity

Ethylene glycol monobutyl ether acetate (112-07-2)

ACGIH: A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans

DFG: Category 4 (no significant contribution to human cancer)

γ -Butyrolactone (96-48-0)

IARC: Monograph 71 [1999]; Supplement 7 [1987]; Monograph 11 [1976] (Group 3 (not classifiable))

Vinyl chloride-Vinyl acetate copolymer (Trade Secret)

IARC: Supplement 7 [1987]; Monograph 19 [1979] (Group 3 (not classifiable))

Mutagenic Data

No information available for the product.

Reproductive Effects Data

Safety Data Sheets

Available data characterizes components of this product as reproductive hazards.

Specific Target Organ Toxicity - Single Exposure

blood, central nervous system, systemic toxicity, kidneys, hematopoietic system

Specific Target Organ Toxicity - Repeated Exposure

blood, kidneys

Aspiration Hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

respiratory disorders

Section 12 - ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Analysis - Aquatic Toxicity

Ethylene glycol monobutyl ether acetate (112-07-2)

Algae: 72 Hr EC50 *Desmodesmus subspicatus*: >500 mg/L

Invertebrate: 48 Hr EC50 *Daphnia magna*: 37 mg/L

Propylene glycol monomethyl ether acetate (108-65-6)

Fish: 96 Hr LC50 *Pimephales promelas*: 161 mg/L [static]

Invertebrate: 48 Hr EC50 *Daphnia magna*: >500 mg/L

γ -Butyrolactone (96-48-0)

Algae: 72 Hr EC50 *Desmodesmus subspicatus*: 360 mg/L; 96 Hr EC50

Desmodesmus subspicatus: 79 mg/L

Invertebrate: 48 Hr EC50 *Daphnia magna* Straus: >500 mg/L

Bioaccumulation

No information available for the product.

Bioconcentration

No information available for the product.

Biodegradation

No information available for the product.

Persistence

No information available for the product.

Mobility

No information available for the product.

Other Information

No additional information is available.

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose in accordance with all applicable regulations.

Component Waste Information

There is no applicable waste information for this product's components.

Section 14 - TRANSPORT INFORMATION

IATA Information

Not regulated as dangerous goods for transport.

ICAO Information

Not regulated as dangerous goods for transport.

Safety Data Sheets

IMDG Information

Not regulated as dangerous goods for transport.

Marine Pollutant

Ethylene glycol monobutyl ether acetate (112-07-2)

IBC Code: Category Y

Propylene glycol monomethyl ether acetate (108-65-6)

IBC Code: Category Z

γ-Butyrolactone (96-48-0)

IBC Code: Category Y

Section 15 - REGULATORY INFORMATION

Singapore Regulations

Component Analysis

Propylene glycol monomethyl ether acetate (108-65-6)

Petroleum and Flammable Materials - Hazard Classes: 3 (regulated under Propylene glycol monomethyl ether acetate); 3

Petroleum and Flammable Materials - Regulated Products:

SCDPEA3272L1 (regulated under Propylene glycol monomethyl ether acetate); SCDMPA1993L2

Component Analysis - Inventory

Component	CAS	US	CA	EU	AU	PHIL	JP	KR	CN	NZ
Ethylene glycol monobutyl ether acetate	112-07-2	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Propylene glycol monomethyl ether acetate	108-65-6	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
γ-Butyrolactone	96-48-0	Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	Yes
Vinyl chloride-Vinyl acetate copolymer	Trade Secret	Yes	DSL	No	Yes	Yes	Yes	Yes	Yes	Yes

Section 16 - OTHER INFORMATION

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; CAS - Chemical Abstracts Service; CLP - Classification, Labelling and Packaging; EEC - European Economic Community; EIN (EINECS) - European Inventory of Existing Commercial Chemical Substances; ELN (ELINCS) - European List of Notified Chemical Substances; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IMDG - International Maritime Dangerous Goods; IBC Code - International Bulk Chemical Code; Kow - Octanol/water partition coefficient; LC50 - Lethal Concentration, 50%; LD50 - Lethal Dose, 50%; LEL - Lower Explosive Limit; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NTP = National Toxicology Program; REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - European Rail Transport; STEL - Short-term Exposure Limit; TWA - Time Weighted Average; UEL - Upper Explosive Limit

Disclaimer

The information set forth in this Safety Data Sheet does not purport to be all-inclusive and should be used only as a guide. While the information and recommendations set forth herein are believed to be accurate, the company



Product Name: CS100 ink Yellow
SDS No. 037-S153420
First issue: 2017/10/20
Revised: 2023/01/10

Safety Data Sheets

makes no warranty regarding such information and recommendations and disclaims all liability from reliance thereon.